

ULTRAFINE COPPER ALLOY WIRE, STRANDED COPPER ALLOY WIRE
CONDUCTOR, EXTRA FINE COAXIAL CABLE, AND PROCESS FOR PRODUCING
ULTRAFINE COPPER ALLOY WIRE

5 FIELD OF THE INVENTION

The invention relates to an ultrafine copper alloy wire,
a stranded copper alloy wire conductor, and an extrafine
coaxial cable each comprising a copper alloy wire with a
diameter of not more than 0.08 mm, and a process for producing
10 the ultrafine copper alloy wire, and more particularly to an
ultrafine copper alloy wire, a stranded copper alloy wire
conductor, and an extrafine coaxial cable possessing excellent
tensile strength, wire drawability, and bending properties, and
a process for producing the ultrafine copper alloy wire.

15 BACKGROUND OF THE INVENTION

A reduction in size of electronic equipment, IC testers,
and medical ultrasound system has led to a demand for a
reduction in diameter of electric wires for these types of
20 equipment. In particular, in the case of electric wires for
medical ultrasound system, there is a demand for cables which
have an increased number of wire cores while maintaining the
outer diameter of conventional cables. Conductors currently in
use in practical applications are mainly 40AWG (7/0.03). Among
25 them, those which have been extensively used in the art are
copper alloy wires comprising an oxygen-free copper (OFC)
having an impurity content of about 10 ppm as a base metal and
a very small amount of tin added to the base metal.

Problems involved in the drawing of a wire rod through dicing are wire breaking attributable to foreign materials and wire breaking attributable to ductile fracture.

Detailed analysis of samples, which have been broken due to the presence of foreign materials, has revealed that the cause of the inclusion of foreign materials is classified roughly into two routes. One of them is foreign materials externally included during wire drawing. The other route is inclusions contained in copper as a material or additive elements or peeled pieces produced by the separation of refractories, such as SiC , SiO_2 , and ZrO_2 , which are components of crucibles and molds, during melting and casting. Among these foreign materials, the inclusion of the former type of foreign materials can be reduced by performing the step of wire drawing in a clean environment. On the other hand, improving the quality of the base material is necessary for reducing the amount of the latter type of foreign materials. For the ductile failure, it is known that this failure is closely related to the level of working. When the level of working is large, the deformation resistance is large and the plastic deformation is less likely to occur. Therefore, ductile failure is likely to occur. However, when the level of working does not reach the working limit, the higher the strength of the material, the lower the susceptibility to the ductile failure. Therefore, materials having higher strength are desired. Thus, in the production of ultrafine wires, very careful attention should be paid so as to avoid the inclusion of foreign materials in each of the steps in the production

process.

An example of a conventional extrafine conductor, which has attempted to solve the problem of wire breaking attributable to foreign materials, is described in Japanese Patent Laid-Open No. 293365/1999.

This extrafine conductor comprises 1 to 4.5% by weight of silver with the balance consisting of copper and unavoidable impurities, and the diameter of foreign materials contained in the extrafine conductor has been brought to a predetermined value or less relative to the diameter of the extrafine conductor. This can realize the provision of extrafine conductors possessing tensile strength, wire drawability, and windability which are high enough to reduce wire breaking during wire drawing and winding. For example, when the diameter of the extrafine conductor is 20 μm , bringing the diameter of the foreign materials to not more than 12 μm can bring about good results.

In the conventional extrafine conductor, however, since the foreign material to be excluded is specified by the diameter of the foreign material, there is a problem that, when the amount of foreign materials having a diameter of not more than the specified diameter is large, wire breaking is likely to occur during wire drawing and, in addition, the bending properties are poor.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide an ultrafine copper alloy wire, a stranded copper alloy wire

conductor, and an extrafine coaxial cable possessing excellent tensile strength, wire drawability, and bending properties, and a process for producing the ultrafine copper alloy wire.

In order to attain the above object, according to the first feature of the invention, an ultrafine copper alloy wire with a diameter of not more than 0.08 mm is constituted by a copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass.

The wire diameter should be not more than 0.08 mm. This is because wires having a diameter exceeding 0.08 mm can be stably produced even when conventional oxygen-free copper (OFC) is used as the base material. The use of high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass can minimize the content of the foreign material, causative of wire breaking, in the base material. The addition of silver to the high-purity copper can improve the tensile strength without a significant lowering in electrical conductivity as compared with the addition of tin, and thus can reduce the ductile failure. Bringing the purity of silver to not less than 99.99% by mass can minimize the contamination of copper as the matrix. The content of silver is limited to 1.0 to 5.0% by mass. When the silver content is less than 1.0% by mass, the amount of eutectic crystal phase crystallized is very small. Therefore, in this case, the effect of improving the strength is poor. When the silver content exceeds 5.0% by mass, work hardening is significant. In this case, cold-drawing

cannot be successfully carried out without providing the step of heat treatment in the course of the drawing of ultrafine conductors having a diameter of not more than 0.02 mm.

In order to attain the above object, according to the second feature of the invention, an ultrafine copper alloy wire with a diameter of not more than 0.08 mm is constituted by a copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.5% by mass of magnesium having a purity of not less than 99.9% by mass.

In addition to silver, magnesium having a purity of not less than 99.9% by mass may be added in an amount of 0.01 to 0.5% by mass. The reason why magnesium is added is that, since silver is expensive, a part of silver is replaced with magnesium as an additive element which does not significantly lower the electric conductivity to lower the silver content. The purity of magnesium is limited to not less than 99.9% by mass from the viewpoint of minimizing the contamination of copper as the matrix. The content of magnesium is limited to 0.01 to 0.5% by mass. When the magnesium content is less than 0.01% by mass, no satisfactory effect can be attained by the addition of magnesium. On the other hand, when the magnesium content exceeds 0.5% by mass, work hardening is significant, and, in this case, cold-drawing cannot be successfully carried out without providing the step of heat treatment in the course of the wire drawing of ultrafine conductors.

In order to attain the above object, according to the third feature of the invention, an ultrafine copper alloy wire with a diameter of not more than 0.08 mm is constituted by a copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.3% by mass of indium having a purity of not less than 99.99% by mass.

In addition to silver, indium having a purity of not less than 99.99% by mass may be added in an amount of 0.01 to 0.3% by mass. The reason why indium is added is that, since silver is expensive, a part of silver is replaced with indium as an additive element which does not significantly lower the electric conductivity to lower the silver content. The purity of indium is limited to not less than 99.99% by mass from the viewpoint of minimizing the contamination of copper as the matrix. The content of indium is limited to 0.01 to 0.3% by mass. When the indium content is less than 0.01% by mass, no satisfactory effect can be attained by the addition of indium. On the other hand, when the indium content exceeds 0.3% by mass, work hardening is significant, and, in this case, cold-drawing cannot be successfully carried out without providing the step of heat treatment in the course of the wire drawing of ultrafine conductors.

The copper alloy wire may have thereon a tin plating, a silver plating, a nickel plating, a tin-lead solder plating, a tin-silver plating, a tin-copper plating, a tin-silver-copper

plating, or a tin-silver-copper-bismuth plating. The adoption of this construction can realize good corrosion resistance and terminal connection when the alloy wire is used as electric wires for equipment.

5 Further, in order to attain the above object, according to the fourth feature of the invention, a stranded copper alloy wire conductor comprises a plurality of copper alloy wires with a diameter of not more than 0.08 mm stranded together, said copper alloy wire comprising high-purity copper having a total
10 unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass.

Stranding a plurality of copper alloy wires together can reduce bending strain when the outer diameter of the conductor
15 is identical. Therefore, the bending fatigue lifetime can be prolonged in applications which is used under repeatedly bent condition.

In order to attain the above object, according to the fifth feature of the invention, a stranded copper alloy wire
20 conductor comprises a plurality of copper alloy wires with a diameter of not more than 0.08 mm stranded together, said copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver
25 having a purity of not less than 99.99% by mass and 0.01 to 0.5% by mass of magnesium having a purity of not less than 99.9% by mass.

Further, in order to attain the above object, according

to the sixth feature of the invention, a stranded copper alloy wire conductor comprises a plurality of copper alloy wires with a diameter of not more than 0.08 mm stranded together, said copper alloy wire comprising high-purity copper having a total
5 unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.3% by mass of indium having a purity of not less than 99.99% by mass.

10 Further, in order to attain the above object, according to the seventh feature of the invention, an extrafine coaxial cable comprises a copper alloy wire with a diameter of not more than 0.08 mm provided for constituting an inner conductor or an outer conductor, said copper alloy wire comprising high-purity
15 copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass.

20 Further, in order to attain the above object, according to the eighth feature of the invention, an extrafine coaxial cable comprises a copper alloy wire with a diameter of not more than 0.08 mm provided for constituting an inner conductor or an outer conductor, said copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more
25 than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.5% by mass of magnesium having a purity of not less than 99.9% by mass.

Further, in order to attain the above object, according to the ninth feature of the invention, an extrafine coaxial cable comprises a copper alloy wire with a diameter of not more than 0.08 mm provided for constituting an inner conductor or an outer conductor, said copper alloy wire comprising high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.3% by mass of indium having a purity of not less than 99.99% by mass.

Further, in order to attain the above object, according to the tenth feature of the invention, a process for producing an ultrafine copper alloy wire, comprises the steps of: melting a high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass in a carbon crucible installed in a vacuum; replacing an atmosphere surrounding the melted copper by an argon gas atmosphere and adding 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass to said copper; casting said copper with silver added thereto in a carbon mold into a wire rod; and drawing said wire rod to a diameter of not more than 0.08 mm.

In this production process, the crucible and mold used are limited respectively to a carbon crucible and a carbon mold. The reason for this is that a major part of foreign materials included during melting and casting is accounted for, for example, by SiC , SiO_2 , and ZrO_2 , which are components of ceramics and cement used in crucibles or molds employed in melting and/or molds used in casting and are separated from the

crucibles and included in the melt.

In order to attain the above object, according to the eleventh feature of the invention, a process for producing an ultrafine copper alloy wire, comprises the steps of: melting a high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass in a carbon crucible installed in a vacuum; replacing an atmosphere surrounding the melted copper by an argon gas atmosphere and adding, to said copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.5% by mass of magnesium having a purity of not less than 99.9% by mass; casting said copper with silver and magnesium added thereto in a carbon mold into a wire rod; and drawing said wire rod to a diameter of not more than 0.08 mm.

Further, in order to attain the above object, according to the twelfth feature of the invention, a process for producing an ultrafine copper alloy wire, comprises the steps of: melting a high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass in a carbon crucible installed in a vacuum; replacing an atmosphere surrounding the melted copper by an argon gas atmosphere and adding, to said copper, 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass and 0.01 to 0.3% by mass of indium having a purity of not less than 99.99% by mass; casting said copper with silver and indium added thereto in a carbon mold into a wire rod; and drawing said wire rod to a diameter of not more than 0.08 mm.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be explained in more detail in conjunction with the appended drawings, wherein:

Fig. 1 is a cross-sectional view of an extrafine coaxial cable according to the first preferred embodiment of the invention; and

Fig. 2 is a cross-sectional view of an extrafine coaxial cable according to the second preferred embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the invention will be described in conjunction with the accompanying drawings. Fig. 1 shows an extrafine coaxial cable according to the first preferred embodiment of the invention. This extrafine coaxial cable comprises: an inner conductor 1 of a conductor size 44AWG composed of a plurality of extrafine copper alloy wires stranded together (seven ultra fine copper alloy wires with a diameter of 0.02 mm stranded together); an insulation 2 which is provided around the inner conductor 1 to insulate the inner conductor 1; an outer conductor 3 provided around the insulation 2, for removing noise, the outer conductor 3 comprising ultrafine copper alloy wires with a diameter of 0.02 mm; and a jacket 4 provided around the outer conductor 3. The insulation 2 may be formed of, for example, a solid fluororesin, more specifically FEP, PFA, or ETFE. In the insulation 2, for example, the outer diameter is 0.115 mm, and the wall thickness is 0.06 mm. The jacket 4 is formed of, for example, PET. In

this jacket 4, for example, the outer diameter is 0.215 mm, and the wall thickness is 0.02 mm.

The material for the ultrafine copper alloy wire used in the inner conductor 1 and the outer conductor 3 is one comprising high-purified copper, plated with a silver plating, having a total unavoidable impurity content of not more than 1 ppm by mass and, added to the high-purity copper, an element, such as silver, magnesium, or indium, having a purity of not less than 99.99% by mass, and examples thereof include Cu - 1.0 to 5.0 mass% Ag, Cu - 1.0 to 5.0 mass% Ag - 0.01 to 0.05 mass% Mg, and Cu - 0.01 to 0.3 mass% In.

This ultrafine copper alloy wire may be produced, for example, by the following process. Here the production of an alloy wire of Cu - 1.0 to 5.0 mass% Ag will be described. At the outset, high-purity copper having a total unavoidable impurity content of not more than 1 ppm by mass is pickled to remove foreign materials adhered onto the surface of the high-purity copper. The pickled copper is then placed in a carbon crucible, and the pickled copper is then vacuum melted in a small continuous casting system. Upon complete melting of copper, the atmosphere in the chamber is replaced by argon gas, and 1.0 to 5.0% by mass of silver having a purity of not less than 99.99% by mass is added to the melt. After silver is completely dissolved in the melt, the melt is held for 10 min, followed by continuous casting by means of a carbon mold to produce a wire rod having a diameter of 0.08 mm. The wire rod is drawn to a diameter of 0.02 mm. Thus, an ultrafine copper alloy wire is produced.

According to the first preferred embodiment described above, since the inner conductor 1 and the outer conductor 3 are formed of an ultrafine copper alloy wire in which the inclusion of foreign materials, causative of wire breaking, in the base material has been minimized, wire breaking is less likely to occur in the step of wire drawing. This contributes to improved productivity, and can provide extrafine coaxial cables possessing excellent bending properties.

Fig. 2 shows an extrafine coaxial cable according to the second preferred embodiment of the invention. The construction of the extrafine coaxial cable shown in Fig. 2 is the same as that of the extrafine coaxial cable according to the first preferred embodiment, except that the inner conductor 1 is constituted by a single-wire conductor formed of an ultrafine copper alloy with a diameter of 0.06 mm which has been produced in the same manner as described above in connection with the first preferred embodiment. The extrafine coaxial cable according to this second preferred embodiment is inferior to that according to the first preferred embodiment in bending properties. However, as with extrafine the coaxial cable according to the first preferred embodiment, in the extrafine coaxial cable according to the second preferred embodiment of the invention, wire breaking is less likely to occur in the step of wire drawing. Therefore, the productivity can be improved.

EXAMPLES

<Examples 1 and 2>

Ultrafine copper alloy wires of Examples 1 and 2 according to the invention were produced as follows. High-purity copper (purity of copper: 99.9999% by mass) as a base material was pickled to remove foreign materials adhered onto the surface of the copper, was set within a carbon crucible, and was vacuum melted in a small continuous casting system. After copper was completely melted, the atmosphere in the chamber was replaced by argon gas. 2% by mass (Example 1) or 5% by mass (Example 2) of silver (purity: 99.99% by mass) was then added to the melt. After silver was completely dissolved in copper, the melt was held for 10 min, followed by continuous casting by means of a carbon mold to produce a wire rod with a diameter of 8.0 mm which was then drawn to a diameter of 0.02 mm.

<Examples 3 to 6>

Ultrafine copper alloy wires of Examples 3 to 6 according to the invention were produced as follows. High-purity copper (purity of copper: 99.9999% by mass) as a base material was pickled to remove foreign materials adhered onto the surface of the copper, was set within a carbon crucible, and was vacuum melted in a small continuous casting system. After copper was completely melted, the atmosphere in the chamber was replaced by argon gas. 2% by mass (Examples 3 and 4) or 5% by mass (Examples 5 and 6) of silver (purity: 99.99% by mass) was then added to the melt. After silver was completely dissolved in copper, the melt was held for 10 min. 0.05% by mass (Examples 3 and 5) or 0.2% by mass (Examples 4 and 6) of magnesium (purity: 99.9% by mass) was then added to the melt, and the

melt was held for additional 10 min. Continuous casting was then carried out by means of a carbon mold to produce a wire rod with a diameter of 8.0 mm which was then drawn to a diameter of 0.02 mm.

5 <Examples 7 to 10>

Ultrafine copper alloy wires of Examples 7 to 10 according to the invention were produced as follows. High-purity copper (purity of copper: 99.9999 % by mass) as a base material was pickled to remove foreign materials adhered onto the surface of the copper, was set within a carbon crucible, and was vacuum melted in a small continuous casting system. After copper was completely melted, the atmosphere in the chamber was replaced by argon gas. 2% by mass (Examples 7 and 8) or 5% by mass (Examples 9 and 10) of silver (purity: 99.99% by mass) was then added to the melt. After silver was completely dissolved in copper, the melt was held for 10 min. 0.01% by mass (Examples 7 and 9) or 0.1% by mass (Examples 8 and 10) of indium (purity: 99.99% by mass) was then added to the melt, and the melt was held for additional 10 min.

Continuous casting was then carried out by means of a carbon mold to produce a wire rod with a diameter of 8.0 mm which was then drawn to a diameter of 0.02 mm.

<Comparative Example 1>

An ultrafine copper alloy wire of Comparative Example 1 was produced as follows. Oxygen-free copper (purity of copper: 99.99% by mass) was melted in a crucible made of SiC or the like in the air. 0.3% by mass of tin (purity: 99.9% by mass) was then added to the melt, and the melt was held for 10 min,

followed by continuous casting and rolling to produce a wire rod with a diameter of 11.0 mm which was then drawn to a diameter of 0.02 mm.

<Comparative Examples 2 and 3>

5 Ultrafine copper alloy wires of Comparative Examples 2 and 3 were produced as follows. Oxygen-free copper (purity of copper: 99.99% by mass) was melted in a crucible made of SiC or the like in the air. 2% by mass (Comparative Example 2) or 5% by mass (Comparative Example 3) of silver (purity: 99.99% by mass) was added to the melt, and the melt was held for 10 min, followed by continuous casting and rolling to produce a wire rod with a diameter of 11.0 mm which was then drawn to a diameter of 0.02 mm.

<Comparative Examples 4 to 7>

15 Ultrafine copper alloy wires of Comparative Examples 4 to 7 were produced as follows. Oxygen-free copper (purity of copper: 99.99% by mass) was melted in a crucible made of SiC or the like in the air. 2% by mass (Comparative Examples 4 and 5) or 5% by mass (Comparative Examples 6 and 7) of silver (purity: 99.99% by mass) was added to the melt, and the melt was held for 10 min. 0.05% by mass (Comparative Examples 4 and 6) or 0.2% by mass (Comparative Examples 5 and 7) of magnesium (purity: 99.9% by mass) was then added to the melt, and the melt was held for additional 10 min, followed by continuous casting and rolling to produce a wire rod. During the drawing of the wire rod, wire breaking attributable to the inclusion of the material constituting the crucible frequently occurred. Therefore, the experiment was ceased.

<Comparative Examples 8 to 11>

Ultrafine copper alloy wires of Comparative Examples 8 to 11 were produced as follows. Oxygen-free copper (purity of copper: 99.99% by mass) was melted in a crucible made of SiC or the like in the air. 2% by mass (Comparative Examples 8 and 9) or 5% by mass (Comparative Examples 10 and 11) of silver (purity: 99.99% by mass) was added to the melt, and the melt was held for 10 min. 0.01% by mass (Comparative Examples 8 and 10) or 0.1% by mass (Comparative Examples 9 and 11) of indium (purity: 99.99% by mass) was then added to the melt, and the melt was held for additional 10 min, followed by continuous casting and rolling. In this case, the surface of the resultant wire rod was deeply cracked. Therefore, the wire rod was judged to be improper as the base material of the ultrafine wire, and the experiment was ceased.

The ultrafine copper alloy wires prepared above were measured for tensile strength (MPa) in the case of drawing to a diameter of 0.02 mm, electrical conductivity (% IACS), and the amount of drawn wire per breaking (kg/break) when 20 kg of the wire was drawn.

The results of measurement are shown in Table 1.

Table 1

Sample	Ag content, mass%	Mg content, mass%	In content, mass%	Sn content, mass%	Impurity content, ppm	Tensile strength, MPa	Electrical conductivity, %IACS	Amount of drawn wire, kg/break
Ex. 1	2.0	-	-	-	< 1	1,030	81	2.22
Ex. 2	5.0	-	-	-	< 1	1,220	70	2.50
Ex. 3	2.0	0.05	-	-	< 1	1,060	78	2.50
Ex. 4	2.0	0.2	-	-	< 1	1,090	76	2.50
Ex. 5	5.0	0.05	-	-	< 1	1,250	66	2.22
Ex. 6	5.0	0.2	-	-	< 1	1,280	64	2.00
Ex. 7	2.0	-	0.01	-	< 1	1,050	79	2.50
Ex. 8	2.0	-	0.1	-	< 1	1,105	78	2.00
Ex. 9	5.0	-	0.01	-	< 1	1,255	68	2.22
Ex. 10	5.0	-	0.1	-	< 1	1,290	67	2.00
Comp. Ex. 1	-	-	-	0.3	17	830	73	1.11
Comp. Ex. 2	2.0	-	-	-	16	1,050	81	1.18
Comp. Ex. 3	5.0	-	-	-	17	1,250	70	1.25

Comp. Ex. 4	2.0	0.05	-	-	15	-	-	-
Comp. Ex. 5	2.0	0.2	-	-	17	-	-	-
Comp. Ex. 6	5.0	0.05	-	-	16	-	-	-
Comp. Ex. 7	5.0	0.2	-	-	15	-	-	-
Comp. Ex. 8	2.0	-	0.01	-	18	-	-	-
Comp. Ex. 9	2.0	-	0.1	-	17	-	-	-
Comp. Ex. 10	5.0	-	0.01	-	16	-	-	-
Comp. Ex. 11	5.0	-	0.1	-	16	-	-	-

Further, ultrafine copper alloy wires prepared in Examples 1 to 4 and Comparative Example 5 were used to prepare samples having structures shown in Figs. 1 and 2. A load of 100 gf was applied to each sample, and a left-and-right 90-degree bending test was carried out under conditions of bending $r = 1$ mm and rate 30 cycles/min.

The test results are shown in Table 2.

Table 2

Sample	Ag content, mass%	Mg content, mass%	In content, mass%	Sn content, mass%	Impurity content, ppm	Bending fatigue lifetime, cycle	
						Fig. 1	Fig. 2
Ex. 1	2.0	-	-	-	< 1	1,950	380
Ex. 2	5.0	-	-	-	< 1	2,300	440
Ex. 3	2.0	0.05	-	-	< 1	2,130	410
Ex. 4	2.0	0.2	-	-	< 1	2,210	425
Comp.							
Ex. 5	-	-	-	0.3	17	1,300	250

As is apparent from Table 1, for the ultrafine copper alloy wires of the examples according to the invention, the amount of drawn wire was improved by approximately twice over that in the comparative ultrafine copper alloy wires. This indicates that the productivity of ultrafine copper alloy wires with a diameter of 0.02 mm has been improved by approximately twice over the productivity of conventional ultrafine copper alloy wires. Further, a not less than 20% improvement in tensile strength could be realized over the conventional copper - 0.3 mass% tin. This could realize materials which are less likely to cause wire breaking attributable to ductile fracture and, at the same time, have electrical conductivity comparable to or better than the conventional materials.

Further, as is apparent from Table 2, the bending fatigue lifetime of the extrafine coaxial cables using the ultrafine copper alloy wires of the examples according to the invention was 50% or more better than the conventional extrafine coaxial cables using copper - 0.3 mass% tin.

The conductor may be one produced by heat treating the conductor formed of one of the ultrafine copper alloy wires prepared in the examples of the invention to regulate the elongation to not less than 5%.

The conductor may be one produced by adding a very small amount of magnesium or indium to a fiber-reinforced metal composed of chromium, iron, niobium or the like added to high-purity copper (99.9999% by mass) and then conducting wire drawing to a size level of ultrafine wires.

As described above, according to the invention, since the

inclusion of foreign materials, causative of wire breaking, in the base material has been minimized, excellent wire drawability and bending properties can be realized. Further, by virtue of the use of silver as an additive element, the tensile strength is excellent.

The invention has been described in detail with particular reference to preferred embodiments, but it will be understood that variations and modifications can be effected within the scope of the invention as set forth in the appended claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2